

Correction to “Design and field experiments of a ground-penetrating radar for Mars exploration” by Carl Leuschen, Pannir Kanagaratnam, Kenji Yoshikawa, Steve Arcone, and Prasad Gogineni

Received 29 April 2003; accepted 29 April 2003; published 3 July 2003.

INDEX TERMS: 0910 Exploration Geophysics: Data processing; 0925 Exploration Geophysics: Magnetic and electrical methods; 0994 Exploration Geophysics: Instruments and techniques; 1823 Hydrology: Frozen ground; 9900 Corrections; *KEYWORDS:* Ground-penetrating radar (GPR), Mars, analog, measurements, permafrost

Citation: Leuschen, C., P. Kanagaratnam, K. Yoshikawa, S. Arcone, and P. Gogineni, Correction to “Design and field experiments of a ground-penetrating radar for Mars exploration,” *J. Geophys. Res.*, 108(E7), 5068, doi:10.1029/2003JE002113, 2003.

[1] In the paper “Design and field experiments of a ground-penetrating radar for Mars exploration” by Carl Leuschen, Pannir Kanagaratnam, Kenji Yoshikawa, Steve Arcone, and Prasad Gogineni (*Journal of Geophysical Research*, 108(E4), 8034, doi:10.1029/2002JE001876, 2003), a Greek mu (μ) was rendered incorrectly in paragraph [40], second sentence. The correct sentence is as follows: “The first is the continuous reflection ranging from about 0.3 μ s to 0.35 μ s.”